

Translations from a vocabulary

Handling translation into various languages

Hans van der Meer

This module was formerly part of `hvdM-xml` but has now been split off into an independent module with its own description. It is used for making other modules language-sensitive and is especially tailored for XML use.

1. Introduction

Elements of the output can be internationalized through the definition and use of one or more vocabularies. This module allows for a flexible and adaptable translation of individual words. The component effectuating this is the module `hvdM-voc`. Its interface is intended to be accessed from XML as well as through ConT_EXt macros.

This module certainly is *not* a full blown translator. Its scope is restricted to the translation of individual words; not even plural forms are automatically translated and therefore must be added separately. Although simplistic in nature, it provides for the automatic adaptation of certain keywords to a change of language.

It all started with the construction of a database in XML format with historical facts about my ancestors. Each fact resided in a separate file to be processed by my note-processing module `hvdM-tak`. Everything is enclosed in an XML node with suitable node names chosen. Since the lingua franca in computing is English, it seemed natural to use this for these names. Thus each person in my notes became to be described by a `<person>` node. For instance:

```
<note>
  <person>
    <name>Arnoldus van der Meer</name>
    <age>28</age>
    <profession>seller of mineral water</profession>
  </person>
  <!-- other nodes -->
</note>
```

Typeset in ConT_EXt with `\language[en]`, such a note looks as in figure 1. Note the English keywords at the left edge corresponding to the node names. The remainder of the text is in Dutch, as might be expected for material taken from five centuries of Dutch archives.

— note-1 — file: events/hga-0402-422-1-99.xml —
subject: Schuldinning door Arnoldus van der Meer
date: 5 November 1779
category: event/weeskamer
key: vandermeer blauwsonnevelt prins
author: Hans van der Meer
source: [Haags Gemeentearchief 0402-01 inv.422 pdf-1 p.9](#)
location: Den Haag
person: Arnoldus van der Meer
role: schuldinner
person: Francina Prins
relation: weduwe van Frederik van Blauwsonnevelt
role: erfgename
person: Frederik van Blauwsonnevelt (Fredrik van Blauwsonnevelt)
relation: overleden van echtgenoot Francina Prins
abstract:
Arnoldus van der Meer neemt op zich om voor de Blauwsonnevelt en hun twee minderjarige kinderen van f325-15 te innen.

Figure 1. Language set to English.

Not all members in my family liked the English words interspersed between the Dutch text; thus arose the idea for this translator. The keywords with their translation were put in a vocabulary as described below. In the notes module, their type-setting is enclosed in a `\translate` macro call. The result is shown in figure 2; again note the keywords at the left edge.

— notitie-1 — file: events/hga-0402-422-1-99.xml —
onderwerp: Schuldinning door Arnoldus van der Meer
datum: 5 november 1779
categorie: event/weeskamer
sleutel: vandermeer blauwsonnevelt prins
auteur: Hans van der Meer
bron: [Haags Gemeentearchief 0402-01 inv.422 pdf-1 p.9](#)
plaats: Den Haag
persoon: Arnoldus van der Meer
rol: schuldinner
persoon: Francina Prins
relatie: weduwe van Frederik van Blauwsonnevelt
rol: erfgename
persoon: Frederik van Blauwsonnevelt (Fredrik van Blauwsonnevelt)
relatie: overleden van echtgenoot Francina Prins
samenvatting:
Arnoldus van der Meer neemt op zich om voor de Blauwsonnevelt en hun twee minderjarige kinderen van f325-15 te innen.

Figure 2. Language set to Dutch.

But (inevitably) I became a bit sloppy. Dutch words crept in as node names for new properties which were added in the course of the genealogical investigations:

```
<note>
  <person>
    <name>...</name>
  </person>
  <samenvatting>an abstract</samenvatting>
</note>
```

Figure 1 shows what happens if the note is typeset in English again. That one key-word *samenvatting* strangely deviates from the others.

```
—— note-1 — file:events/hga-0402-422-1-99.xml ——
subject: Schuldinning door Arnoldus van der Meer
date: 5 November 1779
category: event/weeskamer
key: vandermeer blauwsonnevelt prins
author: Hans van der Meer
source: Haags Gemeentearchief 0402-01 inv.422 pdf-1 p
location: Den Haag
person: Arnoldus van der Meer
  role: schuldinner
person: Francina Prins
  relation: weduwe van Frederik van Blauwsonnevelt
  role: erfgename
person: Frederik van Blauwsonnevelt (Fredrik van Blaau
  relation: overleden van echtgenoot Francina Prins
samenvatting: Arnoldus van der Meer neemt op zich om
erik van Blauwsonnevelt en hun twee minderjarige kind
taal van f325-15 te innen.
```

Figure 3. Language set to English with Dutch node.

Although changing node names to their English equivalents is a simple action in an editor, this problem provided me with the incentive to make the translator module a bit more general. Instead of translating from one language only, it should allow translation between any two languages in the vocabulary. Look at Figure 4 where this flexibility is demonstrated by changing to `\language[de]`.

2. XML interface

Everything starts with the creation and filling of a vocabulary. By default, the module provides a vocabulary to which one can add translations but it is possible to create others, as has been done in the code below. A new vocabulary is created the first time its name appears on a `<vocabulary name="name">` node. Further such calls with that name are silently ignored.

```
— Notiz-1 — Datei: events/hga-0402-422-1-99.xml —  
Thema: Schuldinning door Arnoldus van der Meer  
Datum: 5 November 1779  
Kategorie: event/weeskamer  
Schlüssel: vandermeer blauwsonnevelt prins  
Autor: Hans van der Meer  
Quelle: Haags Gemeentearchief 0402-01 inv.422 pdf-1 p  
Ort: Den Haag  
Person: Arnoldus van der Meer  
Rolle: schuldinner  
Person: Francina Prins  
Beziehung: weduwe van Frederik van Blauwsonnevelt  
Rolle: erfgename  
Person: Frederik van Blauwsonnevelt (Fredrik van Blaau  
Beziehung: overleden van echtgenoot Francina Prins  
Zusammenfassung:  
Arnoldus van der Meer neemt op zich om voor de  
Blauwsonnevelt en hun twee minderjarige kindere  
van f325-15 te innen.
```

Figure 4. Language set to German.

Creation of a vocabulary will *not* make it automatically the current vocabulary. That should be done by the separate set attribute as in the example below.

```
<vocabulary name="myvocab" set="myvocab">  
  <word>  
    <en>dutch</en>  
    <nl>nederlands</nl>  
    <de>niederländisch</de>  
    <fr>néerlandais</fr>  
  </word>  
</vocabulary>
```

Load the above data from a buffer or a file with:

```
<vocabulary buffer="aBuffer"/>  
<vocabulary file="aFile"/>
```

Vocabularies are switched with the set attribute. A value 'default' for the name performs a switch back to the default vocabulary installed by the module.¹ The code below illustrates how to set and retrieve the names of the current vocabulary and language.

```
<vocabulary set="myvocab"/>  
<vocabulary show="vocabulary"/>  
<vocabulary show="language"/>
```

¹ Note that a vocabulary named 'default' cannot be used and will raise an error if one tries to do so.

The results are `vocabulary = myvocab` and `language = en`. Note that attributes `name` and `set` behave differently. When the named vocabulary does not yet exist, the former will create a vocabulary with that name, whereas the latter will issue an error message instead. When both attributes are present, the vocabulary is created first and then made current.

Individual translations can be added to any named vocabulary, but when there is no name attribute on `<vocabulary>` the current vocabulary will be extended.

```
<vocabulary>
  <word>
    <en>greek</en>
    <nl>grieks</nl>
    <de>griechisch</de>
    <fr>grec</fr>
  </word>
</vocabulary>
```

With the current language being `en` this results in `greek`, `Greek` and `GREEK`. Changing the language setting to German with

```
<vocabulary use="de"/>
```

will change to `griechisch`, `Griechisch` and `GRIECHISCH`.

Translations are retrieved by a `<vocabulary>` node with attributes `get`, `Get` and `GET`. The three variants select the corresponding case variants. Presence of a `use` attribute translates into that language but leaves the current language setting unchanged. For instance:

```
<vocabulary get="greek"/>
<vocabulary use="nl" Get="dutch"/>
<vocabulary use="fr" GET="english"/>
```

produces `griechisch`, `Nederlands` and `ANGLAIS`. The presence of a `'get'`-ter forces the change from attribute `use` to be locally confined. Although the last language accessed here was from `use="fr"`, the current language `de` has not changed.

The vocabulary is set up in such a way that translations between all language pairs are possible. In itself that sounds nice, but what if a synonym has to be added? For example, besides `'Dutch'` translated into `'niederländisch'`, we want the two-letter code `'nl'` to be translated into `'niederländisch'` too.

The problem here is the following: Addition of `'nl'` in the same manner as demonstrated above, will overwrite cross translations already present instead of merely adding the equivalents for `'nl'`. The solution is simple. Use `<word add="nl">`, and the enclosed translations will be taken as synonyms. In this manner `'nl'` is added to the vocabulary without generating cross translations. We will find for instance `'nl'`

contextgroup > context meeting 2021

translating into *niederländisch* just as it happens when translating ‘Dutch’ to german.

```
<word add="n1">
  <en>dutch</en>
  <n1>nederlands</n1>
  <de>niederländisch</de>
  <fr>néerlandais</fr>
</word>
```

A problem still remains with this translation scheme. Let us add translations for Icelandic, switch to Dutch and see what `get` and `Get` translations do: *ijslands* and *IJslands*. The latter is wrong, because in Dutch the ‘ij’ counts for one letter! Thus ‘Ijslands’ should have been ‘IJlands’. Luckily the solution is not problematic. Add an extra node for ‘ijsland’ → ‘IJland’ as a synonym with an adapted language code `N1`; the first letter of `n1` now being in uppercase. Instead of raising the first letter of the translation only, the translator then uses the alternative definition:

```
<N1>IJlands</N1>
```

With this addition to the vocabulary we now get *IJslands* as it should be. The same problem arises for letters such as the `ç` in *français* leading to ‘FRANçAIS’ instead of ‘FRANÇAIS’ or the `ä` in ‘Niederländisch’. Here we could have solved it with other exceptions as `<FR>FRANÇAIS</FR>`, but instead the upper-lowercase translator has been made a little bit smarter. It knows how to do a case change for letters like `é`, `à`, `ü`, `ç`.

3. ConTExT interface

Although primarily developed for use in an XML environment, we end up calling `TEX` code. It is therefore always possible to fall back on the underlying macros. The following are the available API calls:

- `\VocabularyCreate[#1]` – creates a vocabulary named in `#1` if it does not yet exist, otherwise do nothing. Note that the current vocabulary is not changed; this should be done explicitly with the `set` macro.
- `\VocabularyDelete[#1]` – use this in the rare case one wishes to get rid of a vocabulary. The default and the current vocabulary cannot be deleted; nor is it possible to remove items from a vocabulary once they have been added.
- `\VocabularySet[#1]` – the vocabulary named `#1` will be made the current one. Reset the module to its default vocabulary by calling it with an empty parameter.
- `\Vocabulary` – the name of the current vocabulary.
Example: the current vocabulary is *myvocab*.

- `\VocabularySetLanguage[#1]` – the two-letter language code makes it the current vocabulary language.² An empty argument will set it to the value of `\currentlanguage`.
- `\VocabularyLanguage` – retrieves the two-letter language code of the current language.
Example: after changing to French by calling `\VocabularySetLanguage[fr]` the current language at this point is *fr*.
- `\VocabularyLoadFromBuffer[#1]`
`\VocabularyLoadFromString[#1]`
`\VocabularyLoadFromFile[#1]` – these macros load data as XML nodes from string, buffer and file.

Example: prepare with `\startbuffer[spanish]` a buffer to add Spanish:

```
<vocabulary>
  <word>
    <en>spanish</en>
    <nl>spaans</nl>
    <de>spanisch</de>
    <fr>espagnol</fr>
  </word>
</vocabulary>
```

and load it with `\VocabularyLoadFromBuffer[spanish]`. Now translation of ‘Spanish’ in *fr* will be *espagnol*. Similarly, use `\VocabularyLoadFromFile[italian.xml]` from the prepared file `italian.xml` and obtain *italien* for ‘Italian’.

- `\translate{#1}`
`\Translate{#1}`
`\TRANSLATE{#1}` – translate the argument into the current language with no case change, first letter uppercase, all letters uppercase, respectively.
Example: `\TRANSLATE{Dutch}` in the current language *fr* results in *DUTCH*. But an absent translation returns its argument unchanged as in `\Translate{Japanese}` is *Japanese*.
- `\VocabularySetLanguageDefault[#1]`
`\VocabularyLanguageDefault`
`\translateDefault[#1]` – There are situations where one language is special. An example is found in the module mentioned in the introduction. Nodes `<author>`, `<person>`, etc. need special treatment in the program. This is accomplished by attaching a flag. Without a common default language, it would have been necessary to flag all occurrences of `<author>`, `<auteur>`, `<Autoi>`, etc. separately. By using `\translateDefault` this can be avoided because it


² Do not be tempted to try ‘Fr’ or ‘FR’ because the module will silently convert both to ‘fr’.

contextgroup > context meeting 2021

enables the programmer to collect all occurrences into a common language. An empty argument `\VocabularySetLanguageDefault[]` sets to the value of `\currentlanguage`. Note that setting of the default language is done globally.

4. Availability

The module and its supporting modules can be downloaded from my site hvandermeer.com/publications.html. The \TeX -stuff resides in section “Articles on \TeX ”, and downloads are a little below in the link called “ConTeXt module distribution”.



Object and photo: Harald König